



Rodin Water Saving Mono Basin CHE Tap (with pop up waste)



The Rodin water saving mono basin mixer tap operates with a single lever and includes a pop-up waste. The tap is supplied with both a water saving aerator and ceramic cartridge. The patented design of the aerator not only introduces more air into the water but it significantly reduces the accumulation of scale and is thus ideal for use in areas of hard water.

Moving the mixer lever upwards/downwards will increase/decrease the flow of water. Moving the mixer lever from right to left will increase the water temperature. Pull the vertical control rod up to close the waste outlet and push down to open.

The tap is fitted with two 300mm flexipipe connections terminating with a 1/2" nut. In order to deck mount the tap a drill hole with a 33mm diameter is required.

Product: Water saving tap with pop up waste (WS EU 8030 CHE)

Finish: Polished chrome

Water pressure: 0.2 bar pressure minimum operating pressure

Flow rates:

Pressure (Bar)	Flow (l/min)
0.5	3.8
1	4.8
2	6.8
3	8

* note the above rates apply only with the Rodin aerator fitted

Installation: These fittings are mixing devices and therefore water supplies must be reasonably balanced. Where connections are made to the mains cold water supply, WRC approved single check valves must be fitted to both hot and cold inlets.



Installation (cont): Before making any inlet pipe connections, all supply pipes **MUST** be thoroughly flushed to remove debris. Failure to do so could result in damage or low flow from the mixer unit.

The fitting of isolating valves to the inlet feeds is advised for ease of maintenance. Please take great care when installing this mixer not to damage its surface.

Maintenance: This product is finished to the highest standard and due care needs to be taken to ensure their looks are retained.

The product should be cleaned with a soft damp cloth **ONLY** and advise strongly against the use of **ALL** cleaning products i.e. powders and liquids.

If the above instructions are not followed this will invalidate your guarantee in the event of a problem occurring.

Warranty: A 5-year warranty is provided against faulty workmanship, or materials, providing:

- It has have been installed, maintained and used in accordance with the manufacturer's instructions and subjected to normal use only.
- The defect is not due to accident, misuse, neglect or repair (other than by the manufacturer) or damage caused by foreign objects or substances.

Line drawing:

